

1. Volume Control

2. XBass®

XBass® was uniquely-designed to extend the bass response to suit different headphones.

- Direct
- For bass shy headphones.
- For average bass headphones.

Tip: To start with, try the "●" setting. If bass response is still insufficient, then try the "●●●" setting.

3. 3D HolographicSound®

3D HolographicSound® recreates a holographic sound field like listening to a pair of speakers.

- Direct
- 3D for flat sounding recordings.
- 3D for recordings with excessive stereo effect.

Tip: For music with more than average emphasis on stereo content (e.g. classical, jazz, rock), try the "●" setting. For flat or mono sounding music (e.g. pop), try the "●●●" setting.

Tip: Each track may require a different XBass® and 3D HolographicSound® settings to sound the best.

Tip: XBass® and 3D HolographicSound® are all based on sophisticated ASP (Analogue Signal Processing) circuits, no sound-damaging DSP (Digital Signal Processing) is used.

ifi warranty

In order to activate the warranty for this iFi product, you must register with the iFi website.

Component :


Serial no:

4. 6.3mm Headphone Jack

Connect headphone.

5. Gain Switches

Setting details and the micro switches to adjust gain are located on the underside of the iCAN.



6. DC Power input

Connect ONLY the iFi iPower ultra low-noise power supply. For maximum power, always use the 15 volt version of the iPower otherwise the full sonic potential of the micro iCAN SE will not be realised.

7. RCA Input

From a music source with RCA connections.

8. 3.5mm Input

From music source equipped with 3.5mm connections.

Tip: Only input should be connected and used at a time.

LEDs

 Ready

 DirectDrive® in operation

 Power on

Specifications

- Gain: 0dB, 12dB and 24dB user-selectable
- Signal to Noise Ratio: >123dB (A)
- Total Harmonic Distortion (THD): <0.003% (400mV/150R)
- Frequency Response: 0.5Hz to 500KHz (-3dB)
- Output Impedance: <1 ohm
- Output Power: >4000mW (16Ω)
- Output Voltage: >10V (>600Ω)
- Input Voltage: AC 100 – 240V, 50/60Hz
- Power Consumption: < 5W idle, 12W max
- Dimensions: 158(l)x68(w)x28(h)mm
- Weight: 216g (0.48 lbs)

Specifications are subject to change without notice.

ifi-audio.com

Ver1.1

Terms & Conditions

iFi guarantees that this iFi product shall be free from defects in materials and workmanship for a period of 1 year for parts and labour.

The warranty period begins at the date of retail sale by an authorized iFi distributor/dealer and is subject to the following requirements and understandings:

- It is the responsibility of the buyer within 30 days from the original sale, to register and activate the product warranty with the iFi website.
- The original invoice must be produced for authentication prior to any warranty claim.
- The iFi product must not have been modified in any manner whatsoever, or the warranty will immediately become void.
- The iFi warranty is only valid in the country of original sale.
- The product must not have been stored in a humid environment; nor subjected to weather, water, or saltwater spray.
- iFi shall not, under any circumstances, be liable for any incidental or consequential damages arising from the loss of property or other damage or losses due to the failure of an iFi product. iFi is not liable for loss of use or inconvenience caused by the failure of an iFi product. iFi is not liable for damage caused to other audio components because of the failure of an iFi product.
- During the warranty period, iFi will repair the product to working order, or, at iFi's option, replace the defective module with a similar available product.
- All repairs performed after expiry of the warranty period will be charged to the owner and will carry a 180-day warranty on parts and labour. The customer is responsible for shipping the unit to the iFi distributor in the original packaging. This includes the payment of any shipping charges and related taxes.
- Should any warranty issues arise, the decision of iFi is full and final.

ifi-audio.com