

1. DC Power input

Connect ONLY the iFi iPower ultra lownoise power supply.

2. EQ Curves Selection

Columbia, RIAA, Decca.








3. RCA Outputs

To amplifier.



4. MC Inputs

Suitable for MC cartridges with an output voltage ≤1mV.

5. Settings Switches

Settings details and the micro switches to adjust them are located on the underside of the iPhono.

6. MM Inputs

Suitable for MM and high-output MC cartridges with an output voltage >1mV.



In order to activate the warranty for this iFi product, you must register with the iFi website.

Component:

Serial no:

Tip: To obtain the best sound, correct settings for gain, load and EQ are required.

Tip: EO Curves

Columbia*: most Columbia/CBS, Epic, EMI (records originally issued under Columbia)

RIAA: standard EQ curve for all records issued after 1980s and some after 1950's.

Decca*: most Decca, London, Deutsche Grammophon (DG), Archiv, EMI, Argo, NAB

* For pre-1980 records

If an LP sounds overly bright, edgy, thin and lacking scale and body via RIAA EQ, please try Decca EQ.

If an LP sounds both too bright and with muddy overblown bass, please try the Columbia EQ.

Tip: There are four different types of RIAA EQ available, eRIAA, IEC, RIAA, eRIAA+IEC. Adjustable via micro switches located on the underside of the iPhono.

LEDs



Ready



Class A TubeState® in operation



Power on

Specifications

• Input Voltage: 15V/0.9A

AC 100 -240V,50/60Hz

• Power Consumption: < 5W

• Dimensions: 180(l) x 67(w) x 28(h) mm

• Weight: 265g (0.58 lbs)

• Warranty period: 12 months

Specifications are subject to change without notice.

ifi-audio.com

Terms & Conditions

iFi guarantees that this iFi product shall be free from defects in materials and workmanship for a period of 1 year for parts and labour.

The warranty period begins at the date of retail sale by an authorized iFi distributor/dealer and is subject to the following requirements and understandings:

- It is the responsibility of the buyer within 30 days from the original sale, to register and activate the product warranty with the iFi website.
 The original invoice must be produced for authentication prior to
- any warranty claim.
- The iFi product must not have been modified in any manner
- The irr brougt must not never been mounted many manner whatsoever, or the warranty will immediately become void.
 The iFi warranty is only valid in the country of original sale.
 The product must not have been stored in a humid environment;
- The product must not have been stored in a humid environment; nor subjected to weather, water, or salvater spray.
 if is hall not, under any circumstances, be liable for any incidental or consequential damages arising from the loss of property or other damage or losses due to the failure of an iFi product. iFi is not liable for loss of use or inconvenience caused by the failure of an iFi product. iFi is not liable for damage caused to other audio components because of the failure of an iFi product.
- components because of the failure of an IFi product.

 During the warranty period, IFi will repair the product to working order, or, at IFI's option, replace the defective module with a similar available product.

 All repairs performed after expiry of the warranty period will be charged to the owner and will carry a 180-day warranty on parts and labour. The customer is responsible for shipping the unit to the IFI distributor in the original packaging. This includes the payment of any shipping the unit parts and related taxes.
- shipping charges and related taxes.

 Should any warranty issues arise, the decision of iFi is full and

ifi-audio.com